48V 50ah 100ah Home Energy Storage Battery Rack Mount Solar System **Lithium Battery**

| Brand Name: Certification: Model Number: Minimum Order Price: Packaging Deta Supply Ability: |
|--|
| Product Speci |
| Battery Type: Output Power F Dimension (L*W Weight: System Type: Type: Communication Grid Connection Product Name: |
| Capacity: Voltage: Max Continuous Current: Bluetooth / Wifi: Communication |

Our Product Introduction

for more products please visit us on enikolnewenergy.com

Basic Information

- Place of Origin: Guangdong, China
- ENIKOL
- MSDS. CE. FCC. UKCA ESK4805CR
- Quantity: 2 sets
 - \$590.00/sets 2-499 sets
 - ails: Colorful box
 - 10000 Set/Sets per Month





ification

| Battery Type: Output Power Range: Dimension (L*W*H): Weight: | LiFePO4 0-5 KWh 442*360*132.5mm 23.5kg | ENIKOL |
|--|---|--------|
| System Type: Type: Communication Port: Grid Connection: Product Name: Capacity: Voltage: | Rack-mounted Split, Rack Mounted Battery CAN, RS485 Off Grid, Hybrid Grid ESK4805CR 50Ah, 2.56KWH 48v | |
| Max Continuous Discharge Current: Bluetooth / Wifi: Communication Function: | Customizable | |

More Images ENIKOL ENIKOL ENIKOL ENIKOL ENIKOL

Product Description

Hot household Energy storage Rack-mount 48v 100ah lithium Battery 50ah 48v solar system battery

Product Parameter

Product Model:

ESK-2420CR ESK-4810CR

ESK-4805CR

Type of Battery:

Lithium Iron Phosphate



for more products please visit us on enikolnewenergy.com

| Battery Assembly Method: | 16S1P | | | |
|--------------------------------------|--|-------------|---------------|--|
| Max parallel: | 64sets | | | |
| Rated capacity: | 200AH(5120WH) | 100AH5120WH | 50AH(2560WH) | |
| Rated voltage : | 25.6v | 51.2v | 51.2v | |
| Charging voltage: | 29.2V | 58.4V | 58.4V | |
| Max charging current : | 10 | 0A | 50A | |
| Max continuous discharge current: | | 100A | | |
| Weight: | 43kg | 43kg | 27kg | |
| Display: | | LCD | | |
| Dimension (L* W * H) mm: | 460*442*117 | 460*442*117 | 442*360*132.5 | |
| Warranty : | | 5 years | | |
| communication faction: | CAN/RS485 or dry contact | | | |
| Cycle life: | | ≥6000 times | | |
| Charging temperature: | | 0 to +55 | | |
| Operating temperature: | | -20 to +65 | | |
| Protection function: | overcharge protection,over discharge protection,over-current protection,short circult protection,over temperature protection and low voltage alarm | | | |
| ENIKOL | | | | |




Our Advantages:

[Matching multiple inverters]: With RS485/CAN communication protocol which can better match with 14 brands of solar inverter(PYLONTECH/GOODWE/Growatt/SMA/Victron/ TBB/Must/Srne/MEGAREVO/Deye/INVT/Voltronic/SOFAR/SOROTEC)

[Smart BMS]: Our lithium battery has a built-in Battery Management System (BMS) to balance all cells, we can ensure consistency and stability during battery use.

[Wide Application]: Suitable for home energy storage, Photovoltaic energy storage projects, Wind energy storage, UPS, Energy storage of base station, Fire emergency equipment, RV, etc.



Guangming District, Shenzhen, Guangdong Province, China